







| 未注公差/General tolerances(mm) |       |       |       |       |       |       |       |       |       |       |       |       |       |
|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0                           | >3    | >6    | >10   | >18   | >30   | >50   | >80   | >120  | >180  | >250  | >315  | >400  |       |
| ~3                          | ~6    | ~10   | ~18   | ~30   | ~50   | ~80   | ~120  | ~180  | ~250  | ~315  | ~400  | ~500  |       |
| ±0.12                       | ±0.18 | ±0.22 | ±0.26 | ±0.31 | ±0.37 | ±0.57 | ±0.80 | ±0.93 | ±1.05 | ±1.15 | ±1.60 | ±2.20 | ±2.50 |

0.1/10  
±2'

View A



|   |         |                 |           |
|---|---------|-----------------|-----------|
| 5 | Spring  | Stainless steel | /         |
| 4 | Clamp   | Copper alloy    | Sn Plated |
| 3 | Button  | PA66            | UL94V-0   |
| 2 | Cover   | PA66            | UL94V-0   |
| 1 | Housing | PA66            | UL94V-0   |

| ITEM   | NAME OF PART | MATERIAL      | NOTES  |        |
|--|--------------|---------------|--------|--------|
| UL 标准/UL Standard:   |              | B             | C      | D      |
| 额定电压/电流/Rated Voltage(V)/Current(A)                              |              | 300/10        | /      | 300/10 |
| IEC 标准/IEC Standard:   |              |               |        |        |
| 过压类别/Overvoltage Category/污染等级/Pollution Degree                  |              | III/3         | III/2  | II/2   |
| 额定电压/电流/Rated Voltage(V)/Current(A)                              |              | /             | 400/20 | /      |
| 额定脉冲电压(KV)/Rate Impulse Voltage(KV)                              |              | /             | 4      | /      |
| 线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG) |              | 0.2~2.5/26~12 |        |        |
| 间距/Pitch(mm)/线数范围/Poles  |              | 7.5/N=02~16P  |        |        |
| 剥线长度/Stripping length(mm)  |              | 9~10          |        |        |
| 使用温度范围/Operating temperature(°C)                                 |              | -40~+105      |        |        |
| 符合RoHS环保要求/Conform to RoHS                                       |              | Yes           |        |        |

|                         |   |            |           |
|-------------------------|---|------------|-----------|
| MATERIAL:               | SURFACE: /  |            |           |
| MAT NO.:                | /   |            |           |
| STATUS:                 | /   |            |           |
| APPD: Li GL 2020.05.26  | NAME: 宁波高松电子有限公司<br>NINGBO DEGSON ELECTRICAL CO., LTD |            |           |
| CHKD: Ma EK 2020.05.26  | 2EDGKD-7.5-XXP-1Y-00A(H)                              |            |           |
| DRFT: LongHM 2019.01.14 | DRAWING NO.: 2EDGKD-7.5-C01                           | REV        | T1        |
| ⊕                       | SIZE: A4  | SCALE: 2:1 | SHEET 1/1 |

| REV | ECN | DESCRIPTION | DRFT | DATE |
|-----|-----|-------------|------|------|
|     |     |             |      |      |