



未注公差/General tolerances(mm)												0.1/10		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315		>400	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/41	150/41	150/15
EC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		630/41	630/41	1000/41
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		6	6	6
间距/Pitch(mm)/线数范围/Poles		7.62/N=02~12P		
使用温度范围/Operating temperature(°C)		-40~+120		
符合RoHS环保要求/Conform to RoHS		Yes		

4	Nut	Steel	M3/Zn Plated
3	Pin header	Copper	Sn plated
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

MATERIAL: /	SURFACE: /		
MAT NO.: /	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
STATUS: /			
APPD: /	NAME: 5EDGRHM-7.62-XXP-1Y-00A(H)		
CHKD: /	DRAWING NO.: 5EDGRHM-7.62-C01		
DRFT: CenMZ 2020.06.09	REV: T0	TO	
SIZE: A4 TYPE: CUSTOMER DRAWING	SCALE: 1.5:1	SHEET	1/1

REV	ECN	DESCRIPTION	DRFT	DATE