



公差等级/General Tolerances(mm)	0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
F0/T2 F0/T8	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±2.50	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Current carrier	Copper	Sn Plated
3	Cage	Copper Alloy	M3\Nt Plated
4	Screw	Copper Alloy	M3\Nt Plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

UL 标准/VII Standard:	B	C	D
额定电压/电势/Rated Voltage(V)/Current(A)	600/20	600/20	600/5
IEC 标准/IEC Standard:			
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特等	III/3	/	/
额定电压/电势/Rated Voltage(V)/Current(A)	800/24	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(Nm/Lbin)	M3, 0.5/4.5		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)	0.2~2.5/24~12		
间距/Pitch(mm)	5.2		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL	/		

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: Li GL 2020.04.02

CHKD: Moo J 2020.04.02

DRAFT:Wang LX 2020.04.02

NAME: **PC2.5-01P-1Y-00A(H)**

DRAWING NO.: PC2.5-C01

TYPE: CUSTOMER DRAWING

SCALE: 2:1

REV T1

1/1

NINGBO DEGSON ELECTRICAL CO.,LTD

宁波高松电子有限公司